

**BUYBOARD QUOTE**  
**CONTRACT #515-16**

*Handwritten initials and numbers: "1000" and "P"*



DATE: January 2, 2019  
QUOTE #:231762-01

TITUS COUNTY PCT 1  
COMMISSIONER: AL RIDDLE  
100 W 1ST ST STE 202  
MOUNT PLEASANT, TEXAS 75455-4443

2016 RM300 HLK030167 0BWR00802 394 HOURS  
**\$437,000.00**

OR

2016 RM300 HLK028541 0BWR00777 1042 HOURS  
**\$396,000.00**

Both of the machines have the SPECS Below

- 366-8343 RM-300 ROTARY MIXER
- 239-7431 CONTROL, GRADE AND STEER MODES
- 500-6034 PRODUCT LINK, CELLULAR PL641
- 234-8895 BOLSTER, REAR WHEEL POWER
- 245-4385 CAB
- 232-2907 DISC, DRIVETRAIN SHEAR
- 255-8201 INSTRUCTIONS, NORTH AMERICAN
- 242-1937 TIRES, FRONT
- 225-4083 TIRES, REAR
- 252-0152 LIGHTS, WORKING
- 234-0308 LIGHTS, ROADING
- 234-0310 LIGHT, WARNING BEACON
- 253-9377 ROPS
- 254-4934 GUARD, POWERTRAIN
- 287-1724 ROTOR, 16" UNIVERSAL
- 433-4400 PUSH BAR
- 253-8758 SPRAY, WATER
- 246-1728 DOOR, FRONT, HYDRAULIC
- 446-5781 ENGINE, NACD ONLY
- 350-0057 MIRRORS
- 349-3528 CAMERA, REAR VISION
- 351-9306 ROTOR, DOOR CAMERA

Thanks,  
Derek Cooper  
HoltCat  
Sulphur Springs, TX 75482  
903-316-7775  
Derek.cooper@holtcat.com

## STANDARD EQUIPMENT

---

### ELECTRICAL

Alarm, back-up  
Alternator, 95-amp  
Batteries, two maintenance free,  
1365 CCA each

Horn, warning (front & rear)  
Starting and charging system, 24-volt  
Product Link Ready

### OPERATOR ENVIRONMENT

Access ladder, left side  
Fixed operator station, left side  
Monitoring system with lighted, analog  
style gauges  
Tachometer with digital hour meter  
Feet/meters per minute indicator  
Engine coolant, hydraulic oil temp  
Engine oil pressure, fuel level,  
voltage indicator  
Platform handrails / guardrails

Power steering, hydraulic  
Propel console with speed control dial,  
padded armrest  
Seat, vinyl, suspension, rotating,  
flip-up armrests  
Seat belt, retractable, 3" (76 mm) wide  
Steering wheel, tilting and telescoping  
Throttle control, two-position, elect  
Vandalism guard for control consoles  
Warning system, action light and horn

### POWERTRAIN

CAT C-11 diesel, ACERT, 6-cylinder,  
turbocharged engine, 350 HP (261 kW)  
U.S. EPA Tier 3 and EU Stage IIIA  
certified  
Air cleaner, dry-type dual element with  
precleaner  
Air-to-air after cooler (ATAAC)  
Belt, serpentine, automatic tensioner  
Demand fan  
Fuel filter / water separator  
Fuel priming pump, electric

Ground level engine shutdown  
Muffler  
Propel system - Front Wheel Drive  
Single propel pump  
Two-speed, axial piston hydraulic  
motors (2) with 2F/2R speeds  
Heavy-duty wheel, planetary gearsets  
Brakes, oil-bath, sealed at each wheel  
Secondary parking brake switch  
Engine load/speed control, automatic  
Steering, front and rear wheels

### ROTOR DRIVE SYSTEM

Axle, heavy-duty  
Clutch, drive, hydraulically actuated  
Dual sealed chain cases  
Self-lubricating  
Single strand drive chains

Heavy-duty shear disc  
Maintenance free u-joint drive shafts  
Transmission, 3-speed, powershift  
(electric, fingertip control)

### OTHER STANDARD EQUIPMENT

Doors, service access, hinged  
Ecology drains  
Electrical system  
Circuit breakers and disconnect switch  
Machine diagnostic connector  
Machine Security System wire-ready

Oil cooler  
Pressure test ports, quick-connect  
Rear door, rotor chamber, hydraulic  
with position indicator  
Rotor hood and rear door lock up device  
Rotor hood side access doors

Starting receptacle for emergency  
start, ground level  
Engine enclosure, steel  
Fuel tank with sediment drain,  
279 gal (1056 L)  
Hitch, front bumper with pin  
Hydraulic system  
Filters, grouped, ground level service

Rotor axle and transmission oil coolers  
Sight gauges (engine coolant, hydraulic  
oil level, rotor axle, air filter  
restriction indicator)  
S.O.S. sampling ports  
Transport tie-down and lift points  
Vandalism protection caplocks  
Variable volume mixing chamber

**ANTIFREEZE**

50% Extended Life Coolant for freeze

protection to -29F (-34C)

**BUYBOARD QUOTE**  
**CONTRACT #515-16**



DATE: January 2, 2019  
 QUOTE #:231762-01

TITUS COUNTY PCT 1  
 COMMISSIONER: ALLEN RIDDLE  
 100 W 1ST ST STE 202  
 MOUNT PLEASANT, TEXAS 75455-4443

One (1) New Caterpillar Inc Model: RM300 Reclaimer/Mixer with all standard equipment in addition to the additional specifications listed below:

**MACHINE SPECIFICATIONS**

STOCK NUMBER: HLK031037      SERIAL NUMBER: 0BWR00851      YEAR: 2018      HOURS: 4

| DESCRIPTION                    | REF.#    |
|--------------------------------|----------|
| RM-300 ROTARY MIXER            | 366-8343 |
| CONTROL, GRADE AND STEER MODES | 239-7431 |
| PRODUCT LINK, CELLULAR PL641   | 500-6034 |
| BOLSTER, REAR WHEEL POWER      | 234-8895 |
| CAB                            | 245-4385 |
| DISC, DRIVETRAIN SHEAR         | 232-2907 |
| INSTRUCTIONS, NORTH AMERICAN   | 255-8201 |
| TIRES, FRONT                   | 242-1937 |
| TIRES, REAR                    | 225-4083 |
| LIGHTS, WORKING                | 252-0152 |
| LIGHTS, ROADING                | 234-0308 |
| LIGHT, WARNING BEACON          | 234-0310 |
| ROPS                           | 253-9377 |
| GUARD, POWERTRAIN              | 254-4934 |
| ROTOR, 16" UNIVERSAL           | 287-1724 |
| PUSH BAR                       | 433-4400 |
| SPRAY, WATER                   | 253-8758 |
| DOOR, FRONT, HYDRAULIC         | 246-1728 |
| ENGINE, NACD ONLY              | 446-5781 |
| MIRRORS                        | 350-0057 |
| CAMERA, REAR VISION            | 349-3528 |
| ROTOR, DOOR CAMERA             | 351-9306 |
| LANE 3 ORDER                   | 0P-9003  |

STANDARD EQUIPMENT LISTED ON PAGE 3

---

|              |              |
|--------------|--------------|
| SALE PRICE   | \$461,483.50 |
| EXT WARRANTY | Included     |
| TOTAL PRICE  | \$461,483.50 |

---

|       |              |
|-------|--------------|
| TOTAL | \$461,483.50 |
|-------|--------------|

---

**WARRANTY**

Standard Warranty: 12 Month/Unlimited Hours Total Machine

**Extended Warranty: 48 MONTH/4000 HOUR POWERTRAIN + HYDRAULICS + TECH**

Thanks,  
Derek Cooper  
HoltCat  
Sulphur Springs, TX 75482  
903-316-7775  
Derek.cooper@holtcat.com

## STANDARD EQUIPMENT

---

### ELECTRICAL

Alarm, back-up  
Alternator, 95-amp  
Batteries, two maintenance free,  
1365 CCA each

Horn, warning (front & rear)  
Starting and charging system, 24-volt  
Product Link Ready

### OPERATOR ENVIRONMENT

Access ladder, left side  
Fixed operator station, left side  
Monitoring system with lighted, analog  
style gauges  
Tachometer with digital hour meter  
Feet/meters per minute indicator  
Engine coolant, hydraulic oil temp  
Engine oil pressure, fuel level,  
voltage indicator  
Platform handrails / guardrails

Power steering, hydraulic  
Propel console with speed control dial,  
padded armrest  
Seat, vinyl, suspension, rotating,  
flip-up armrests  
Seat belt, retractable, 3" (76 mm) wide  
Steering wheel, tilting and telescoping  
Throttle control, two-position, elect  
Vandalism guard for control consoles  
Warning system, action light and horn

### POWERTRAIN

CAT C-11 diesel, ACERT, 6-cylinder,  
turbocharged engine, 350 HP (261 kW)  
U.S. EPA Tier 3 and EU Stage IIIA  
certified  
Air cleaner, dry-type dual element with  
precleaner  
Air-to-air after cooler (ATAAC)  
Belt, serpentine, automatic tensioner  
Demand fan  
Fuel filter / water separator  
Fuel priming pump, electric

Ground level engine shutdown  
Muffler  
Propel system - Front Wheel Drive  
Single propel pump  
Two-speed, axial piston hydraulic  
motors (2) with 2F/2R speeds  
Heavy-duty wheel, planetary gearsets  
Brakes, oil-bath, sealed at each wheel  
Secondary parking brake switch  
Engine load/speed control, automatic  
Steering, front and rear wheels

### ROTOR DRIVE SYSTEM

Axle, heavy-duty  
Clutch, drive, hydraulically actuated  
Dual sealed chain cases  
Self-lubricating  
Single strand drive chains

Heavy-duty shear disc  
Maintenance free u-joint drive shafts  
Transmission, 3-speed, powershift  
(electric, fingertip control)

### OTHER STANDARD EQUIPMENT

Doors, service access, hinged  
Ecology drains  
Electrical system  
Circuit breakers and disconnect switch  
Machine diagnostic connector  
Machine Security System wire-ready

Oil cooler  
Pressure test ports, quick-connect  
Rear door, rotor chamber, hydraulic  
with position indicator  
Rotor hood and rear door lock up device  
Rotor hood side access doors

Starting receptacle for emergency  
start, ground level  
Engine enclosure, steel  
Fuel tank with sediment drain,  
279 gal (1056 L)  
Hitch, front bumper with pin  
Hydraulic system  
Filters, grouped, ground level service

Rotor axle and transmission oil coolers  
Sight gauges (engine coolant, hydraulic  
oil level, rotor axle, air filter  
restriction indicator)  
S.O.S. sampling ports  
Transport tie-down and lift points  
Vandalism protection caplocks  
Variable volume mixing chamber

**ANTIFREEZE**

50% Extended Life Coolant for freeze

protection to -29F (-34C)