

BUYBOARD QUOTE
CONTRACT #515-16



DATE: January 26, 2019
QUOTE #:232412-01

TITUS COUNTY PCT 1
AL RIDDLE
100 W 1ST ST STE 202
MOUNT PLEASANT, TEXAS 75455-4443

One (1) Caterpillar Inc Model: CS54B with all standard equipment in addition to the additional specifications listed below:

MACHINE SPECIFICATIONS

STOCK NUMBER: TXU101211		SERIAL NUMBER: L4H00612	YEAR: 2015	HOURS: 1150
347-9531	CS54B VIBRATORY COMPACTOR			
0P-1870	CERTIFICATE OF ORIGIN			
203-4717	TIRES, FLOTATION, 8PR			
347-9582	ENGINE, TIER 4 CERTIFIED			
354-5413	MIRRORS, REARVIEW, EXTERNAL			
355-2658	SCREEN, STD			
355-2660	GUARD, TRANSMISSION			
355-2671	INSTRUCTIONS, NORTH AMERICAN			
355-3038	PRODUCT LINK, PL321, ROPS/FOPS			
355-3056	LIGHTS, NIGHTTIME			
355-3542	FREQUENCY, FIXED			
356-1226	SEAT, VINYL			
356-2162	PLATFORM, ROPS/FOPS			
360-0494	SCRAPER, STEEL, FRONT & REAR			
362-4940	OIL, HYDR, FACTORY FILLED			
364-8295	SENSOR, DRIVE POWER			
382-8081	AXLE, WITHOUT BRAKES			
382-9003	SEAT BELT, 2"			
108D	CLEAN EMISSIONS MODULE	TIER 4 - INTERIM		
351-8377	ENGINE AR PRIM			

ALSO INCLUDED
FACTORY NEW-- ELLIOT GRID ROLLER SHELL KIT
***SMOOTH DRUM MADE READY TO ACCEPT ELLOIT GRID SHELL**
36 MONTH-1500HOUR-POWERTRAIN & HYDRAULIC WARRANTY

SALE PRICE	\$126,500.00
EXT WARRANTY	Included
TOTAL PRICE	\$126,500.00
<hr/>	
SUB TOTAL	\$126,500.00
TOTAL PURCHASE PRICE	\$126,500.00

FREIGHT TO TITUS COUNTY BARN ALSO INCLUDED IN PRICE

WARRANTY

Extended Warranty: **36MONTH OR 1500HOUR-POWERTRAIN & HYDRAULIC WARRANTY (Starts when delivered),**

Thanks,
Derek Cooper
HoltCat
903-316-7775
Derek.cooper@holtcat.com
Sulphur Springs & Texarkana

STANDARD EQUIPMENT

ELECTRICAL

Alarm, back-up	Horn, warning (front & rear)
Alternator, 95-amp	Starting and charging system, 24-volt
Batteries, two maintenance free, 1365 CCA each	Product Link Ready

OPERATOR ENVIRONMENT

Access ladder, left side	Power steering, hydraulic
Fixed operator station, left side	Propel console with speed control dial, padded armrest
Monitoring system with lighted, analog style gauges	Seat, vinyl, suspension, rotating, flip-up armrests
Tachometer with digital hour meter	Seat belt, retractable, 3" (76 mm) wide
Feet/meters per minute indicator	Steering wheel, tilting and telescoping
Engine coolant, hydraulic oil temp	Throttle control, two-position, elect
Engine oil pressure, fuel level, voltage indicator	Vandalism guard for control consoles
Platform handrails / guardrails	Warning system, action light and horn

POWERTRAIN

CAT C-11 diesel, ACERT, 6-cylinder, turbocharged engine, 350 HP (261 kW) U.S. EPA Tier 3 and EU Stage IIIA certified	Ground level engine shutdown
Air cleaner, dry-type dual element with precleaner	Muffler
Air-to-air after cooler (ATAAC)	Propel system - Front Wheel Drive
Belt, serpentine, automatic tensioner	Single propel pump
Demand fan	Two-speed, axial piston hydraulic motors (2) with 2F/2R speeds
Fuel filter / water separator	Heavy-duty wheel, planetary gearsets
Fuel priming pump, electric	Brakes, oil-bath, sealed at each wheel
	Secondary parking brake switch
	Engine load/speed control, automatic
	Steering, front and rear wheels

ROTOR DRIVE SYSTEM

Axle, heavy-duty	Heavy-duty shear disc
Clutch, drive, hydraulically actuated	Maintenance free u-joint drive shafts
Dual sealed chain cases	Transmission, 3-speed, powershift (electric, fingertip control)
Self-lubricating	
Single strand drive chains	

OTHER STANDARD EQUIPMENT

Doors, service access, hinged	Oil cooler
Ecology drains	Pressure test ports, quick-connect
Electrical system	Rear door, rotor chamber, hydraulic with position indicator
Circuit breakers and disconnect switch	Rotor hood and rear door lock up device
Machine diagnostic connector	Rotor hood side access doors
Machine Security System wire-ready	

Starting receptacle for emergency start, ground level
Engine enclosure, steel
Fuel tank with sediment drain, 279 gal (1056 L)
Hitch, front bumper with pin
Hydraulic system
Filters, grouped, ground level service

- Rotor axle and transmission oil coolers
- Sight gauges (engine coolant, hydraulic oil level, rotor axle, air filter restriction indicator)
- S.O.S. sampling ports
- Transport tie-down and lift points
- Vandalism protection caplocks
- Variable volume mixing chamber

ANTIFREEZE

50% Extended Life Coolant for freeze

protection to -29F (-34C)